

KRÖLL TOWER CRANES





MODEL	K-70	K-160	K-180	K-220	K-260	K-320	K-420	K-560	K-100L	K-125L	K-200L
SPECIFICATIONS											
Max. jib length (ft)	148	197	197	197	197	246	262	295	148	164	164
Min. jib length (ft)	39	102	102	102	102	112	115	115	92	92	92
Min. reach (ft)	7	10	10	11	11	11	11/16	11/16	13	15	16
Load (lbs) Reach (ft)	2650 148	3970 197	5070 197	6620 197	7720 197	7060 246	7720 262	5510 295	4410 148	4410 164	7720 164
Max. load (lbs) Max. reach (ft)	11025 42	22050 47	22050 59	26460 64	26460 71	35280 66	66150 58	66150 72	13230 56	18963 43	22050 82
Height under hook (standard mast) (ft)	135	180	220	194	213	226	269	269	131	180	207
Standard mast dim. □	3'11"	5'3"	5'3"	7'3"	7'3"	7'3"	7'7"	7'7"	5'3"	5'3"	7'3"
Floor climbing equipment	CS12	CS16	CS16	CL22	CL22	CL22	CL23	CL23	CS16	CS16	CL22
Telescopic equipment	CT12	CT16	CT16	CT22	CT22	CT22	CT23	CT23	CT16	CT16	CT22
Standard rail gauge (ft)	15	20	20	20	20	20	30	30	20	20	20
Standard wind speed (mph)	In service Out of service	45 94	45 94	45 94	45 94	45 94	45 94	45 94	45 94	45 94	45 94

The table above denotes the main characteristics of the production series for year 2001.
It is for use as a guidance only, and can be adjusted to suit site requirements.

KRØLL Technical Services will provide you with a more defined load,
reach, height specification to allow for a maximum load reach coverage at a minimum cost.

In addition to the above, quotations can be given for tower cranes of all ton-meter capacities up to 25000 tm.

KRØLL CRANES A/S

Nordkranvej 2 . DK-3540 Lyngø . Denmark . Phone: +45 48 18 74 00 . Fax: +45 48 18 88 07
E-mail: krollcranes@krollcranes.dk . www.krollcranes.com

A MEMBER OF



MUHIBBAH ENGINEERING



KRØLL MAXI RANGE



MODEL	K-800	K-1000	K-1400	K-1800	K-2500	K-3000	K-5000	K-10000	K-25000
SPECIFICATIONS									
Max. jib length (ft)	256	256	262	262	295	295	295	328	328
Min. jib length (ft)	138	138	138	138	138	157	157	197	197
Min. reach (ft)	23	23	23	30	30	30	30	33	33
Load (lbs) Reach (ft)	21800 256	24300 256	36200 262	37500 262	48500 295	59500 295	110000 295	209500 328	441000 328
Max. load (lbs) Max. reach (ft)	66150 92	66150 108	66150 157	88200 131	88200 197	132300 154	220500 164	264600 269	882000 187
Height under hook (standard mast) (ft)	276	256	236	197	236	197	295	295	328
Standard mast dim. □	10'6"	10'6"	13'2"	16'5"	16'5"	16'5"	26'3"	26'3"	32'10"
Telescopic equipment	TS32	TS32	CT40	CT40	TS50	TS50	TS80	TS80	TS100
Standard rail gauge (ft)	30	30	30	30	39	39	39	59	72
Portals (nominal rail gauge)	30	30	30	30	39	39	39	59	72
Standard wind speed (mph)	In service Out of service	45 94	45 94	45 94	45 94	45 94	45 94	45 94	45 94

The listed cranes are a guide to the ton-meter range that KRØLL have designed and produced over the years.

**FOR THE POSSIBILITIES
OF
MAKING HEAVY LIFTS**

KRØLL CRANES A/S

Nordkranvej 2 . DK-3540 Lyngø . Denmark . Phone: +45 48 18 74 00 . Fax: +45 48 18 88 07
E-mail: krollcranes@krollcranes.dk . www.krollcranes.com

A MEMBER OF



MUHIBBAH ENGINEERING